


Anschlagpunkte GK8

Anschlagpunkt ohne Feder

- 180° Schwenkbar




Artikelnummer	Tragfähigkeit in kg	Maße in mm						Gewicht in kg
		B	C	D	E	F	L	
APC1120S	1 120	41	39	13	76	37	36	0,40
APC2000S	2 000	42	40	14	78	48	40	0,46
APC3200S	3 150	45	43	17	89	46	42	0,70
APC5000S	5 300	55	60	22	113	53	50	1,50
APC8000S	8 000	70	71	26	138	67	65	2,50
APC15000S	15 000	97	90	34	182	92	90	5,90

Anschlagpunkt mit Feder

- 180° Schwenkbar

- mit Feder, welche den Bügel unbelastet positioniert



Artikelnummer	Tragfähigkeit in kg	Maße in mm						Gewicht in kg
		B	C	D	E	F	L	
APFC1120S	1 120	41	39	13	76	37	36	0,40
APFC2000S	2 000	42	40	14	78	48	40	0,46
APFC3200S	3 150	45	43	17	89	46	42	0,70
APFC5000S	5 300	55	60	22	113	53	50	1,50
APFC8000S	8 000	70	71	26	138	67	65	2,50
APFC15000S	15 000	97	90	34	182	92	90	5,90

Wir verfügen auch über andere Größen und Hersteller!